



2 FXO Ports Wireless Router FPX9102H



Features Key

- 2 FXO Ports
- Support Asterisk
- TR069 & Auto-provision
- 10/100/1000Mbps Ethernet
- Supports 5GHz & 2.4GHz

Hardware Interface



Overview

FPX9102H network management type dual FXO port wireless VoIP router is one of the most popular converged gateway products developed and produced in the era of Flyingvoice. This product can not only provide users with 2 FXO ports for connecting phone lines, but also provide two external line concurrent call functions. The built-in asterisk also supports 50 extension numbers, which can be used as a small PBX to meet the call needs of small and medium enterprises. Five Gigabit Ethernet ports and dual-band 1200Mbps wireless can simultaneously provide the requirements of wired / wireless connection in the office; the USB 2.0 interface is connected to a U disk and can be used as a TFTP server or Samba server to provide file storage

and transmission functions. The black body is simple and elegant, and the business shape is more suitable for business use. It supports automatic discovery and zero-configuration IP terminals for user deployment. It is also compatible with most network service providers, supports automatic configuration, and TR069 remote management. Small businesses, home offices, remote offices, and multi-branch businesses provide a low-cost, easy-to-use IP voice phone solution.

Technical Parameters

| | |
|------------------|--|
| Power | <ul style="list-style-type: none">AC/DC Adapter<ul style="list-style-type: none">AC Input: 100~240V, 50~60HzDC Output: 12V, 2A |
| Operating System | <ul style="list-style-type: none">Linux 2.6.36 |
| Interfaces | <ul style="list-style-type: none">1 RJ-45 Gigabit WAN port4 RJ-45 Gigabit LAN ports2 RJ-11 FXO ports1 USB 2.0 PortReset key |
| Button | <ul style="list-style-type: none">Power buttonReset button |
| Environmental | <ul style="list-style-type: none">Operation Temperature: -5~45 Degree CStorage Temperature: -25~ 85 Degree CRelative Humidity: 10%~90% No Condensing |
| Audio Codec | <ul style="list-style-type: none">G.711(A/u), PAMS>4.3G.729A/AB, PAMS>4.0T.30 FAX with G.711Adaptive Jitter BufferVoice Activity DetectionComfort Noise GenerationEcho Cancellation |
| Wireless | <ul style="list-style-type: none">Support 802.11 b/g/n 300Mbps MIMOSupport 802.11 a/an/ac 867Mbps MIMO8 SSIDSecurity Mode: OPENWEP (64/128bit), WPA-PSK/WPA2-PSK, WPA-PSK, WPA2-PSKAP Isolation and MBSSID AP IsolationWMMWDSStation listMAC Filter(different from wired MAC Filter) |
| Management | <ul style="list-style-type: none">Firmware UpgradeWeb Management InterfaceLocal and Remote Syslog (RFC3164)Auto ProvisionSNTP Time SynchronizationMulti User LevelSNMPv2TR069Network diagnosis |

| | |
|-----------------------|--|
| Protocols | <ul style="list-style-type: none">• SIP V2.0 (RFC 3261)• Backward compatible with RFC2543• Session timer (RFC4028)• SDP (RFC2327)• RTP/RTCP (RFC1889/RFC1890)• NAPTR for SIP URI lookup (RFC2915)• STUN (RFC2030)• ARP/RARP (RFC 826/903)• SNTP (RFC 2030)• DHCP/PPPoE• HTTP Server for Web Management• TFTP/HTTP/HTTPS for Auto Provision• Message Waiting Indicator (RFC3842)• DHCP Option Codes for SIP (RFC3361)• DNS/DNS SRV (RFC1706 and RFC 2782)• TR069 (TR098,TR104)• IEEE802.1Q VLAN/802.1p/DSCP• SNMP v2 |
| Applications | <ul style="list-style-type: none">• Support Asterisk<ul style="list-style-type: none">Support 50 extensionsSupport 25 concurrent callsSupport voice conference roomSIP trunkIVR• VPN: PPTP, L2TP, OpenVPN• DDNS• QoS• Static route• Firewall• 2 PSTN Trunks (FXO ports) |
| FXO port features | <ul style="list-style-type: none">• Busy tone detection• No current streak detection• Voice interrupt detection• One-time dialing• Dial two times• PSTN Outside Port Poll• Supports reverse polarity signal• FAS (Fake billing correction)• AC / DC impedance configuration• Caller ID (Bellcore Type 1 & 2,ETSI, DTMF) |
| Dimensions And Weight | <ul style="list-style-type: none">• 153mm(L)x153mm(W)x35mm(H)• 330g(N.W) |
