

Grand stream FXO 4 PORT



DESCRIPTION

The GXW410x is a Grand stream 4 Port FXO gateway that enables businesses of all sizes to create and deploy a VoIP and analog hybrid solution. This FXO gateway makes deployments easy by seamlessly connect multiple locations and all devices within an office to any hosted or on-premise IP PBX network. This PRI Gateway is interoperable with PBX, EPABX with IP trunk, IP PBX and Call center software.

Features:

- 4 port FXO gateways
- 10/100 Mbps network ports
- Comprehensive codec support, caller ID, flexible dial plans and security protection
- Designed and tested for full interoperability with leading IP-PBXs, soft-switches and SIP-based environments
- PSTN Failover on power failure.

Technical Specification:





Brand	Grandstream
Key Features	SRTP security encryption technology, Provisioning options include TFTP and HTTP, PSTN Failover on power failure, Supports T.38 Fax for creating Faxover-IP, Supports a wide range of caller ID formats, IP Signalling - SIP (RFC 3261), LED indicators, TFTP and HTTP provisioning
Interfaces	Telephone Interfaces: 4RJ11 FXO port Network Interfaces: 10M/100Mbps, dual RJ45 ports
Management	Syslog support, HTTPS, telnet, remote mamangement using web browser
Mounting	Desktop and Wall mount
Power	Output: 12VDC Input: 100-240VAC / 50- 60Hz
Environmental	Operational: 32-104°F or 0-40°C Storage: 14-140°F or -10-60°C Humidity: 10-90% Noncondensing
Dimension	230mm x 135mm x 35mm (LxWxH)

